



LED Tube T8



Ref#: AB10335-11207

PRODUCT DESCRIPTION

LED T8 Linear Replacement Lamps are the ideal energy saving choices when upgrading traditional linear T8. Universal voltage 120V-277Vac. Compatible with electronic ballast.

Ordering Information

Example: T809xx9-FW06-GL

SPECIFICATION

Dimension(L" x DIA"): 23.78" X 1.00"
47.75" x 1.00"
Max. Weight: 0.68 lbs

Figure	Watts	Color	CCT	Size	Type
T8	09-9 Watts	FW- Frost	30 - 3000K	06-2FT	GL
T8	12-12 Watts	White	35 - 3500K	12-4FT	Glass
	14-14 Watts		40 - 4000K		
	17-17 Watts		45 - 4500K		
			50 - 5000K		

* Special Order- Ask Customer Service for Details

SPECIFICATIONS

	120-277Vac	120-277Vac	120-277Vac	120-277Vac
Voltage	120-277Vac	120-277Vac	120-277Vac	120-277Vac
Power	9W	12W	14W	17W
Color Temperature	3000K/3500K/4000K/4500K/5000K	3000K/3500K/4000K/4500K/5000K	3000K/3500K/4000K/4500K/5000K	3000K/3500K/4000K/4500K/5000K
Power Factor	0.9	0.9	0.9	0.9
Lumen Output	1150lm	1800lm	1800lm	2200lm
LPW	100	106	106	107
CRI	Ra>80	Ra>80	Ra>80	Ra>80
Beam Angle	160°	160°	160°	160°
Harmonic Distortion	15%	15%	15%	15%
Base Type	G13 (Double-Ended)	G13 (Double-Ended)	G13 (Double-Ended)	G13 (Double-Ended)
Life Time	50000H	50000H	50000H	50000H
Operating Temperature	-68°F~104°F	-68°F~104°F	-68°F~104°F	-68°F~104°F
Operation Environment	Indoor	Indoor	Indoor	Indoor
Dimension(L-W-H)	Φ1" * 23.78	Φ1" * 47.76"	Φ1" * 47.76"	Φ1" * 47.76"
Weig (lbs)	0.68lb	0.68lb	0.68lb	0.68lb
Standard	UL/FCC/RoHS	UL/FCC/RoHS	UL/FCC/RoHS	UL/FCC/RoHS